

University of Groningen

Skeletonization methods for image and volume inpainting

Sobiecki, Andre

IMPORTANT NOTE: You are advised to consult the publisher's version (publisher's PDF) if you wish to cite from it. Please check the document version below.

Document Version

Publisher's PDF, also known as Version of record

Publication date:

2016

[Link to publication in University of Groningen/UMCG research database](#)

Citation for published version (APA):

Sobiecki, A. (2016). *Skeletonization methods for image and volume inpainting*. [Thesis fully internal (DIV), University of Groningen]. University of Groningen.

Copyright

Other than for strictly personal use, it is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license (like Creative Commons).

The publication may also be distributed here under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license. More information can be found on the University of Groningen website: <https://www.rug.nl/library/open-access/self-archiving-pure/taverne-amendment>.

Take-down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Downloaded from the University of Groningen/UMCG research database (Pure): <http://www.rug.nl/research/portal>. For technical reasons the number of authors shown on this cover page is limited to 10 maximum.

STELLINGEN

behorende bij het proefschrift

SKELETONIZATION METHODS FOR IMAGE AND VOLUME INPAINTING

van

ANDRÉ SOBIECKI

1. Overall image restoration quality depends mainly on the accuracy of detection of the damaged regions in the images.
2. To help algorithm designers pinpoint and next solve current limitations of skeletonization methods, a promising direction is to devise new metrics for the quantitative comparison of desired skeleton-quality criteria.
3. For the advection skeletonization method described in Chapter 8 of this thesis, modulating the input-surface density by curvature or application-specific metrics would allow different feature-sensitive skeleton simplifications.
4. Inpainting techniques works best for relatively thin or elongated regions.
5. Skeletonization methods can be effectively used to identify thin and elongated areas such hairs in digital images.
6. An interesting and novel application of 3D skeletonization is for inpainting of 3D shapes, where this method has been shown to produce better results than classical morphological operations for gap removal .